



# GUARDIAN G25RMV100

## 50W Mobile Radio



# GUARDIAN™

THE VITAL CONNECTION

## Project 25 Compliant

Government ▪ Military ▪ Public Safety ▪ Business



### High Resolution Display

High-output display can be read easily in tactical situations and blacked-out during covert operations

### Large Diameter Speaker

High-output loudspeaker to override industrial, highway and siren noise

### Tx/Rx Indicator

### Easy Grip Knobs

Large rotary knobs make volume adjustment and channel selection easy

### Programming Keys

Simple to customize - three keys and toggle switch

### Software Defined Keys

### Ext/Both/Int Speaker Switch & Indicator

The Guardian G25RMV100 VHF P25 conventional mobile by Datron is a feature rich, state-of-the-art radio designed for government, public safety and business applications. Fully digital, Guardian meets APCO Project 25 FDMA common air interface standard for compatibility with other Project 25 radios. Guardian also operates as an analog radio, offering full backward compatibility with conventional wideband FM systems. Use it with today's analog wideband radio systems and be ready for tomorrow's digital narrowband world — all in one great package!

- **Multi-Mode** analog and digital, wideband and narrowband, up to 4 banks, 16 zones and 256 channels total (314 channel optional)
- **Shadow Channels** allow communication using any mode - wide or narrowband, analog or digital, crypto or plain
- **Full VHF Bandsread** 136-174 MHz
- **Cloning** radio-to-radio programming
- **Secure Transmissions** Analog, OFB DES, and AES Encryption options
- **OTAR** Over the Air Re-Key
- **GPS/Data** Send GPS coordinates using Datron's optional GPS Microphone
- **Low Power** surveillance mode for covert operations



**Contact us today: 760.597.1500**  
3030 Enterprise Ct, Vista, CA 92081  
sales@dtwc.com ▪ www.dtwc.com

## GUARDIAN G25RMV100 50W Mobile Radio



### MODEL DESIGNATION

### GUARDIAN 50W MOUNT MOBILE RADIO

Datron Model Number	G25RMV100
Frequency Range	136.000 -174.000 MHz
Banks, Zones, Channels, Shadow	4 banks, 16 zones, 256 channels, 7 shadow
Voice Digital Mode Voice Coding	IMBETM 4.4 kb
Frame Re-sync Interval	180 msec
Error Correction Method	RS, golay, hamming
Input Voltage	13.8 Vdc, negative chassis ground
Current Drain @13.8V:	
Standby	0.5 amp
Receive @Rated Audio	3.0 amp
Transmit @Rated Power	14.0 amp
Mounting	Under dashboard using bracket
Dimensions (HxWxD)	2.94 "x 7.13" x 7.06"
Weight	Approximately 5 lbs.
Case	Metal and plastic
Temperature Range	-30°C to +60°C
Channel Spacing	12.5 and 25KHz, selectable in 2.5 or 3.125 KHz steps
FCC Type Acceptance Number	B3TG25RMV100, parts 74, 80, 90, 210
Industry Canada	41091-25RMV100

### RECEIVER (MEASUREMENTS PER TIA/EIA 603C STANDARDS)

Sensitivity		
Digital Mode:	5%BER	-116 dBm or better
Analog Mode:	12 dB SINAD	-116 dBm or better
Spurious		-73.6 dB
Intermodulation		-79.0 dB
Audio Output Power		5 Watts internal, 10 Watts external speaker
Audio Distortion (at 1000 Hz)		5% @ rated power
Maximum Frequency Separation		Full-band split
Spurious Response Attenuation		75dB
Adjacent Channel Selectivity		Analog 58dB, Digital 66.4dB
RX Conducted Spurious Emissions		-92.7dBm

### TRANSMITTER (MEASUREMENTS PER TIA/EIA 603C STANDARDS)

RF Power Output		10/20/35/50 watts, selectable: low power surveillance mode
FM Hum & Noise (wide/narrowband)		-40/34 dB
FCC Modulation Designators		11K0F3E, 16K0F3E, 12K6F1E
Audio Distortion (at 1000 Hz)		±3%
Audio Response (1000 Hz Ref.)		± 3 dB 300 - 3000 (EIA/TIA 603)
Frequency Stability (-30 °C to 60°C)		± 0.6 ppm
Maximum Frequency Separation		Full-band split
TX Unwanted Emissions (Conducted)		-91dB

### GUARDIAN DES ENCRYPTION

Encryption Keys	16
Code Key Generator	External
SBCF Analog DES Encryption	Standard feature
OFB Digital DES Encryption	Optional
AES Digital Encryption	Optional
OTAR	Optional

### ADDITIONAL OPTIONS

GPS Data Transmission	Optional
-----------------------	----------

### ENVIRONMENTAL SPECIFICATIONS MIL-STD-810F

TEST	METHOD	PROCEDURE
Low Pressure (Altitude)	500.4	II
High Temperature	501.4	I, II
Low Temperature	502.4	I
Temperature Shock	503.4	I
Solar Radiation (Sunshine)	505.4	I
Humidity	507.4	I
Salt Fog	509.4	I
Sand and Dust	510.4	I, II
Vibration	514.5	I
Shock	516.5	I

### OPTIONAL FEATURES:

#### Fire Features

Adds an additional bank of 3 zones (48 additional channels), Custom Clone, Tone Pick List, P-25 Talkgroup Picklist and P-25 ID Pick List

#### GPS

Send/Receive GPS coordinates to track personnel and assets. Standard NEMA string at 4800 baud compatible with standard mapping software and custom applications

#### OTAR

Over the Air Re-Key. Change encryption keys over the air without the need to connect to a computer or key fill device.

**AES** P-25 Advanced Encryption Standard

**DES** OFB- P-25 Digital Encryption Standard

### ACCESSORIES

#### Audio:

G25AMM001	PALM MICROPHONE STANDARD
G25AMM002	PALM MICROPHONE DTMF
G25AMM003	DESK MICROPHONE
G25AMS001	EXTERNAL SPEAKER UP TO 15W

#### Mounting:

G25AML001	MOUNTING BRACKET
G25AMG001	POWER CABLE 14 FT.

#### Antennas:

G25AMA001	ANTENNA KIT, MOBILE, 136-144MHZ
G25AMA002	ANTENNA KIT, MOBILE, 144-152MHZ
G25AMA003	ANTENNA KIT, MOBILE, 152-162MHZ
G25AMA004	ANTENNA KIT, MOBILE, 162-172MHZ
G25AMA005	ANTENNA KIT, MOBILE, BROADBAND

#### Remote:

G25TRU001	4 WIRE TONE REMOTE UNIT
G25TRU002	TONE REMOTE LOCAL CONTROL
G25TRU003	TONE REMOTE PROGRAMMING KIT
G25TRU004	TONE REMOTE CONSOLE

Specifications subject to change without notice or obligation.